

WT-5729 Floor marking tape ESD antistatic premium

PRODUCT AND APPLICATION DESCRIPTION

The PREMIUM ESD floor marking tape is designed for permanent and durable marking in static-sensitive areas. It ensures reliable adhesion even under high mechanical stress thanks to its particularly strong adhesive strength. The antistatic function is specially designed for long-term effectiveness and the tape is abrasion-resistant and can be removed without leaving any residue if required.

- Retains its antistatic function in the long term thanks to high-quality PET lamination
- No stretching during use
- Equipped with ESD function on both sides
- For smooth indoor floors
- Hard-wearing and suitable for pedestrians and pallet trucks



TECHNICAL DATA

Material:	Vinyl with PET laminate
Thickness: (without Liner)	0,16 mm ± 0,1
Liner:	Siliconpaper
Surface resistance:	Surface: <math><1.0 \times 10^9 \Omega</math>, Glue: <math><1.0 \times 10^{10} \Omega</math>
Surface:	Highly glossy
Adhesive:	Acrylat
Adhesive property:	Permanent
Temperature range:	-20°C to +70°C
Processing temperature:	≥12°C
Available colors:	Yellow

MORE INFORMATION

To achieve optimum adhesion, the substrate must be free of release agents such as grease, oil, surfactants, dirt and dust. Store in a dry and UV-protected place at 10°C to 25°C.

Note

The product information listed above has been compiled to the best of our knowledge and is based on current data. The properties mentioned are typical but therefore do not constitute a specification. The information provided does not relieve the customer of his obligation to test for suitability for the intended applications and processes. All specifications are subject to change without notice. Colour variations are possible.