

WT-4153 Double-sided adhesive tape

PRODUCT AND APPLICATION DESCRIPTION

Double-sided adhesive tape with a rubber adhesive and a special paper as adhesive backing. The tape is suitable for short-term fixing, bonding, mounting and fastening in production processes, especially where removal without damaging the substrate surfaces after processing is required, such as mounting rubber and photopolymer plates in the printing industry. But also for temporary fixings of items such as nameplates, signs and emblems.

- | Can be used for indoor areas
- | Good adaptability to irregular surfaces



TECHNICAL DATA

Carrier material:	Special paper
Thickness: (without liner)	0.19 mm \pm 0.01 mm
Liner:	Glassine paper
Adhesive:	Rubber
Adhesion:	1.2 kg / 25 mm
Temperature range:	-10 °C to +60 °C
Application temperatur:	\geq 12 °C
Available colours:	Transparent

FURTHER INFORMATION

To achieve optimum adhesion, the substrate must be free of release agents such as grease, oil, surfactants, dirt and dust. Glue without tension, press on carefully, stronger pressure increases the adhesion. Store in a dry and UV-protected place at +5 °C to +25 °C.

Note

The product information listed above has been compiled to the best of our knowledge and is based on current data. The properties mentioned are typical but therefore do not constitute a specification. The information provided does not relieve the customer of his obligation to test for suitability for the intended applications and processes. All specifications are subject to change without notice. Colour variations are possible.