

WT-4210 Double-sided adhesive tape

PRODUCT AND APPLICATION DESCRIPTION

Double-sided adhesive tape with very high adhesive strength. It is suitable for bonding ABS plastic parts in the automotive industry, EPDM or rubber components, furniture modules and decorative trim, battery housings, mirrors and touch displays for electronic devices. WT-4210 is suitable for all smooth and also rough plastics and metals.

- | Can be used for indoor and outdoor areas
- | Very high shear force



TECHNICAL DATA

Carrier material:	PET-foil
Thickness: (without liner)	0.205 mm
Liner:	Red MOPP liner
Adhesive:	Acrylic
Adhesion to steel:	20 min: ≥18 N / 24 mm
Temperature range:	Up to +60 °C
Application temperatur:	+21 °C to +38 °C
Available colours:	Transparent

FURTHER INFORMATION

To achieve optimum adhesion, the substrate must be free of release agents such as grease, oil, surfactants, dirt and dust. Glue without tension, press on carefully, stronger pressure increases the adhesion. Store in a dry and UV-protected place at +5 °C to +25 °C.

Note

The product information listed above has been compiled to the best of our knowledge and is based on current data. The properties mentioned are typical but therefore do not constitute a specification. The information provided does not relieve the customer of his obligation to test for suitability for the intended applications and processes. All specifications are subject to change without notice. Colour variations are possible.