

WT-4211 Double-sided adhesive tape

PRODUCT AND APPLICATION DESCRIPTION

Double-sided, highly transparent adhesive tape with high adhesive strength. It is suitable for thin and highly transparent bonding to many plastics and Plexiglas. Universal use for applications on steel, painted steel and computer hard drives.

Can be used indoors and outdoors



TECHNICAL DATA

Carrier material:	PET-Foil
Thickness: (without liner)	0.14 mm
Liner:	Polyester film
Adhesive:	Acrylic
Adhesion to steel:	700 gf / 10 mm
Shearing force:	4.5 kgf / cm ²
Temperature range:	Up to +120 °C
Application temperatur:	+18 °C to +25 °C
Available colours:	Transparent

FURTHER INFORMATION

To achieve the optimal adhesive strength, the substrate must be free from separating agents such as greases, oils, surfactants, dirt and dust. Immediately after unrolling, apply the tape to the surface and press it down firmly. The storage has to be dry and UV-protected between +5 °C and +25 °C.

Note

The product information listed above has been compiled to the best of our knowledge and is based on current data. The properties mentioned are typical but therefore do not constitute a specification. The information provided does not relieve the customer of his obligation to test for suitability for the intended applications and processes. All specifications are subject to change without notice. Colour variations are possible.