

WT-4217 Double-sided adhesive tape

PRODUCT AND APPLICATION DESCRIPTION

Double-sided adhesive tape with very high adhesive strength on many plastics and metals with a smooth surface. The tape is used for sticking signs made of metal or plastic and is suitable for kisscut and punched part production.

- | Suitable for indoor use
- | Good temperature, chemical and UV resistance



TECHNICAL DATA

Carrier material:	PET-foil
Thickness: (without liner)	0.15 mm ± 0.01 mm
Liner:	Paper liner
Adhesive:	Acrylic
Adhesion:	2.1 kg / 25 mm
Temperature range:	-30 °C to +120 °C
Application temperatur:	≥ 12 °C
Available colours:	Transparent

FURTHER INFORMATION

To achieve optimum adhesion, the substrate must be free of release agents such as grease, oil, surfactants, dirt and dust. Glue without tension, press on carefully, stronger pressure increases the adhesion. Store in a dry and UV-protected place at +5 °C to +25 °C.

Note

The product information listed above has been compiled to the best of our knowledge and is based on current data. The properties mentioned are typical but therefore do not constitute a specification. The information provided does not relieve the customer of his obligation to test for suitability for the intended applications and processes. All specifications are subject to change without notice. Colour variations are possible.