

WT-4320 Double sided adhesive tape

PRODUCT AND APPLICATION DESCRIPTION

WT-4320 is an adhesive tape with fabric reinforcement. It is primarily used as an installation system for dry and whole-surface bonding of standard floor coverings in the fields of object renovation, event technology and trade fair construction.

- | Can be used for indoor areas
- | High initial adhesion
- | Very high plasticizer and aging resistance



TECHNICAL DATA

Carrier material:	Special fabric
Thickness: (without liner)	0.22 – 0.24 mm
Liner:	Silicone coated paper, white
Adhesive:	Polyacrylate based adhesive
Shear resistance:	1000 g/625 mm ²
Peeling resistance:	>5 N/25 mm
Temperature range:	-30 °C to +120 °C
Application temperature:	+5 °C to +30 °C
Available colors:	White

FURTHER INFORMATION

To achieve the optimal adhesive strength, the substrate must be free from separating agents such as greases, oils, surfactants, dirt and dust. The storage has to be dry and UV-protected between +15 °C and +24 °C.

Note

The product information listed above has been compiled to the best of our knowledge and is based on current data. The properties mentioned are typical but therefore do not constitute a specification. The information provided does not relieve the customer of his obligation to test for suitability for the intended applications and processes. All specifications are subject to change without notice. Colour variations are possible.