

WT-4342 Double-sided adhesive tape with textile carrier

PRODUCT AND APPLICATION DESCRIPTION

WT-4342 is designed to provide good adhesion to fibre surfaces. It consists of a laminated fabric backing coated on both sides with a high performance pressure sensitive adhesive and protected with a yellow glassine paper release liner. Areas of application are metal and mould making, woodworking, milling, model making and carpet laying.

- | Can be used for indoor areas
- | Easy to tear by hand



TECHNICAL DATA

Carrier material:	Cloth
Thickness: (without liner)	0.31 mm ±0.04
Liner:	Yellow glassine paper
Adhesive:	Natural rubber
Adhesion to steel:	1 kgf/ 25 mm
Tensile force:	10 kgf/ 25 mm
Available colours:	White

FURTHER INFORMATION

To achieve the optimal adhesive strength, the substrate must be free from separating agents such as greases, oils, surfactants, dirt and dust. Immediately after unrolling, apply the tape to the surface and press it down firmly. The storage has to be dry and UV-protected between +5 °C and +25 °C.

Note

The product information listed above has been compiled to the best of our knowledge and is based on current data. The properties mentioned are typical but therefore do not constitute a specification. The information provided does not relieve the customer of his obligation to test for suitability for the intended applications and processes. All specifications are subject to change without notice. Colour variations are possible.