

WT-4710 Double-sided adhesive tape

PRODUCT AND APPLICATION DESCRIPTION

Double-sided adhesive tape with a high adhesive strength and tear-resistant film backing. The WT-4710 adheres very well to painted and rough surfaces. It is very suitable for bonding backlight modules of LCD displays, nameplates and metal parts.

- | Can be used for interior areas
- | Very good initial adhesion and high tack
- | Very good UV, plasticiser, weathering and ageing resistance



TECHNICAL DATA

Carrier material:	PVC
Thickness: (without liner)	0.225 mm
Liner:	Braunes Pergamin
Adhesive:	Acrylic
Adhesion on steel:	20 min: 16 N / 24 mm
Application temperatur:	+21 °C to +38 °C
Available colours:	White

FURTHER INFORMATION

To achieve optimum adhesion, the substrate must be free of release agents such as grease, oil, surfactants, dirt and dust. Glue without tension, press on carefully, stronger pressure increases the adhesion. Store in a dry and UV-protected place at +5 °C to +25 °C.

Note

The product information listed above has been compiled to the best of our knowledge and is based on current data. The properties mentioned are typical but therefore do not constitute a specification. The information provided does not relieve the customer of his obligation to test for suitability for the intended applications and processes. All specifications are subject to change without notice. Colour variations are possible.