

WT-5020 Dirt resistant floor marking tape

PRODUCT AND APPLICATION DESCRIPTION

Durable, long-lasting, self-adhesive floor marking tape. The Tape is particularly for apolar, moist and cold surfaces in deep-freeze areas. The WT-5020 is extra thin, tear-resistant, quick to apply, wear resistant and has an anti-slip surface with slip resistance R12 .

- | Ideal for ground markings in the freezer area
- | Bonding during cooling mode at up to -20 °C
- | For smooth floor indoor
- | Suitable for pedestrians



TECHNICAL DATA

Material:	Plastic foil
Thickness: (without Liner)	0.4 mm
Liner:	Silicone paper
Surface:	Glossy
Slip-class:	R12 according to DIN 51130
Adhesive:	Acrylic
Adhesive property:	Permanent
Temperature resistance:	-40 °C to +90 °C
Application temperature:	min. -20 °C
Available colours:	Single-colour, multi-colour, individually printed



MORE INFORMATION

It is possible to drive over the belt with floor conveyors. Turning and twisting on the tape with floor conveyors or similar heavy vehicles must be avoided and can lead to the destruction of the tape.

To achieve optimum adhesion, the substrate must be free of release agents such as grease, oil, surfactants, dirt and dust. Store in a dry and UV-protected place at 10°C to 25°C.

Note

The product information listed above has been compiled to the best of our knowledge and is based on current data. The properties mentioned are typical but therefore do not constitute a specification. The information provided does not relieve the customer of his obligation to test for suitability for the intended applications and processes. All specifications are subject to change without notice. Colour variations are possible.