

## WT-5110 Universal space marker

### PRODUCT AND APPLICATION DESCRIPTION

The easy adhesion and high durability make the WT-5110 the ideal marking for warehouses and sales rooms as a marking for workplaces or storage areas.

- | For smooth floors in indoor areas
- | Suitable for pedestrians
- | Suitable for concrete screed smooth, EP / Pu / MMA coatings and tile



### TECHNICAL DATA

Colors:	Plain	Multicolor/ custom printed
Material:	PVC	PVC
Thickness: (without liner)	0,6 mm	0,6 mm
Liner:	Silicone paper	Silicone paper
Surface:	Matt	Slightly glossy, embossed
Adhesive:	Acrylic	Acrylic
Adhesion property:	Permanent	Permanent
Temperature range:	-20 °C to +70 °C	-20 °C to +70 °C
Processing temperature:	≥12 °C	≥12 °C

### WEITERE INFORMATIONEN

To achieve the optimal adhesive strength, the substrate must be free from release agents such as greases, oils, surfactants, dirt and dust. The storage should be dry and UV-protected between 10°C and 25°C.

#### Note

The product information listed above has been compiled to the best of our knowledge and is based on current data. The properties mentioned are typical but therefore do not constitute a specification. The information provided does not relieve the customer of his obligation to test for suitability for the intended applications and processes. All specifications are subject to change without notice. Colour variations are possible.