

WT-5125 Universal floor marking tape

PRODUCT AND APPLICATION DESCRIPTION

The easy adhesion and high durability make the WT-5125 the ideal floor marking for warehouses and sales rooms, path marking and as a marking for workplaces or parking spaces.

- | For smooth indoor floors
- | Suitable for pedestrians
- | Suitable for concrete screed smooth, EP / PU / MMA coatings and tiles



TECHNICAL DATA

Colorus:	Single-colour	multi-colour, individually printed
Material:	PVC	PVC
Thickness: (without Liner)	0.6 mm	0.6 mm
Liner:	Silicone paper	Silicone paper
Surface:	Matte	Slightly glossy, embossed
Adhesive:	Acrylic	Acrylic
Adhesive property:	Permanent	Permanent
Temperature resistance:	-20 °C to +70 °C	-20 °C to +70 °C
Application temperature:	≥12 °C	≥12 °C

MORE INFORMATION

To achieve optimum adhesion, the substrate must be free from release agents such as grease, oil, surfactants, dirt and dust. Store in a dry and UV-protected place at 10°C to 25°C.

Note

The product information listed above has been compiled to the best of our knowledge and is based on current data. The properties mentioned are typical but therefore do not constitute a specification. The information provided does not relieve the customer of his obligation to test for suitability for the intended applications and processes. All specifications are subject to change without notice. Colour variations are possible.