

WT-5160 Standard floor marking tape

PRODUCT AND APPLICATION DESCRIPTION

WT-5160 is a 0.16 mm thick soft PVC tape with pressure sensitive rubber adhesive. It combines good mechanical strength, easy transverse tearing and abrasion resistance with excellent conformability for path marking and flooring. It is used as a hazard warning and for safety marking of potential danger zones.

- | For smooth floors in indoor and protected outdoor environments
- | Excellent resistance to abrasion, corrosion and moisture
- | Suitable for pedestrian
- | Suitable for concrete screed smooth, EP / PU / MMA coatings and tiles
- | Conforms to EU Directive 2000/53 (lead, chromium VI, mercury and cadmium free)



TECHNICAL DATA

Material:	Soft PVC
Thickness: (without Liner)	0.16 mm
Surface:	Matte
Adhesive:	Rubber adhesive
Adhesive property:	Excellent adhesion
Tensile strength: (CEI EN 60454):	≥25 N/cm
Temperature resistance:	-20 °C tp +120 °C
Application temperature:	≥12 °C
Available colours:	Black, yellow, white, red, blue, light green, yellow/black, white/red

MORE INFORMATION

To achieve optimum adhesion, the substrate must be free from release agents such as grease, oil, surfactants, dirt and dust. Store in a dry and UV-protected place at 10°C to 25°C.

Note

The product information listed above has been compiled to the best of our knowledge and is based on current data. The properties mentioned are typical but therefore do not constitute a specification. The information provided does not relieve the customer of his obligation to test for suitability for the intended applications and processes. All specifications are subject to change without notice. Colour variations are possible.