

WT-5224 Strips for floor marking

PRODUCT AND APPLICATION DESCRIPTION

The marking strips can be applied quickly and easily thanks to the mounting film and save time and money. They are ideal for heavy use and have very good adhesion to the ground. If a strip is damaged, it can be replaced quickly.

- | For smooth indoor floors
- | Suitable for pedestrians and lift trucks
- | Suitable for concrete screed smooth, EP / PU / MMA coatings and tiles



TECHNICAL DATA

Material:	PET
Thickness: (without Liner)	0.2 mm
Liner:	Silicone paper
Surface:	Glossy
Adhesive:	Acrylic
Adhesive property:	Permanent or removable
Temperature resistance:	-20 °C to +120 °C
Application temperature:	≥12 °C
Available colours:	Single-colour, multi-colour, individually printed

MORE INFORMATION

It is possible to drive over the belt with floor conveyors. Turning and twisting on the tape with floor conveyors or similar heavy vehicles must be avoided and can lead to the destruction of the tape.

To achieve optimum adhesion, the substrate must be free of release agents such as grease, oil, surfactants, dirt and dust. Store in a dry and UV-protected place at 10°C to 25°C.

Note

The product information listed above has been compiled to the best of our knowledge and is based on current data. The properties mentioned are typical but therefore do not constitute a specification. The information provided does not relieve the customer of his obligation to test for suitability for the intended applications and processes. All specifications are subject to change without notice. Colour variations are possible.