

WT-5229 Dirt resistant floor marking tape

PRODUCT AND APPLICATION DESCRIPTION

Durable, long-lasting, self-adhesive floor marking tape. Ideal for dry areas, quick to apply, wear resistant, easy to clean and can be walked on immediately. The WT-5229 is extra thin, tear-resistant and is particularly suitable for hygiene, food and cleanroom areas.

- | For smooth floor indoor
- | Suitable for pedestrians
- | Suitable for concrete screed smooth, EP / PU / MMA coatings and tiles



TECHNICAL DATA

Version:	5229	5229.1	5229.2
Material:	PET	PET	PET
Thickness: (without Liner)	0.2 mm	0.2 mm	0.2 mm
Liner:	Silicone paper	Silicone paper	Silicone paper
Surface:	Glossy	Glossy	Glossy
Adhesive:	Acrylic	Acrylic	Acrylic
Adhesive property:	Permanent (strong adhesive)	Removable	Permanent (slightly adhesive)
Temperature resistance:	-20 °C to +120 °C	-20 °C to +120 °C	-20 °C to +120 °C
Application temperature:	≥12 °C	≥12 °C	≥12 °C
Available colours:	Single-colour, multi-colour, individually printed	Single-colour, multi-colour, individually printed	Single-colour, multi-colour, individually printed

MORE INFORMATION

It is possible to drive over the belt with floor conveyors. Turning and twisting on the tape with floor conveyors or similar heavy vehicles must be avoided and can lead to the destruction of the tape. To achieve optimum adhesion, the substrate must be free of release agents such as grease, oil, surfactants, dirt and dust. Store in a dry and UV-protected place at 10°C to 25°C.

Note

The product information listed above has been compiled to the best of our knowledge and is based on current data. The properties mentioned are typical but therefore do not constitute a specification. The information provided does not relieve the customer of his obligation to test for suitability for the intended applications and processes. All specifications are subject to change without notice. Colour variations are possible.