

WT-5361 Flat crepe tape

PRODUCT AND APPLICATION DESCRIPTION

WT-5361 consists of a one-side impregnated, tear-resistant, tough crepe paper, coated with a soft, highly heat-resistant, natural rubber adhesive. Therefore WT-5361 also meets the high demands placed on an adhesive tape for automotive varnishing. The tape's adhesive strength and adhesion are specially designed to meet the requirements of automotive painters, decorators and plasterers. It is used in the automotive painting sector for all masking purposes, including oven drying.

- ! Can be used for indoor areas
- ! Stable against moisture and tight against varnishes and paints



TECHNICAL DATA

Carrier material:	Paper / impregnated 60 g/m ²
Thickness: (without liner)	0.135 mm
Adhesive:	Natural rubber crosslinked
Adhesive strength on steel:	2,6 N/cm
Tensile strength:	32 N/cm
Temperature range:	up to +120°C
Application temperature:	≥12 °C
Available colors:	Yellow

FURTHER INFORMATION

To achieve the optimal adhesive strength, the substrate must be free from separating agents such as greases, oils, surfactants, dirt and dust. The storage has to be dry and UV-protected between +5 °C and +25 °C.

Note

The product information listed above has been compiled to the best of our knowledge and is based on current data. The properties mentioned are typical but therefore do not constitute a specification. The information provided does not relieve the customer of his obligation to test for suitability for the intended applications and processes. All specifications are subject to change without notice. Colour variations are possible.