

WT-5415 Anti-slip tape, black, roughly elastic

Slip resistant surface

PRODUCT AND APPLICATION DESCRIPTION

WT-5415 „roughly elastic“ is a non-scuffing anti-slip tape suitable for wet areas. Due to the finely structured anti-slip coating without mineral grain, it is therefore particularly foot-friendly. The tape has a more pronounced surface profile than WT-5415 soft. The anti-slip tape is particularly stable, resilient and easy to clean. Furthermore, it is characterised by its high scratch resistance and durability.

- | For smooth surfaces indoors
- | For slip-resistant finishing of sanitary areas, barefoot zones, gyms, showers, swimming pools or on boats
- | For slip protection in transport and logistics



TECHNICAL DATA

Carrier material:	PVC
Thickness: (without liner)	1.4 mm ± 0.3 mm
Liner:	Silicone paper
Adhesive:	Acrylic
Adhesive strength:	2.3 kg/inch
Slip resistance:	Slip resistant surface
Temperature resistance:	-30°C to +70°C
Application temperature:	≥ 12°C
Available colours:	Black

MORE INFORMATION

To achieve optimum adhesion, the substrate must be free from release agents such as greases, oils, surfactants, dirt and dust. The use of an adhesive primer is required on the following surfaces: concrete and asphalt, untreated, unpainted wood, and on all rough, grained surfaces. Store in a dry and UV-protected place at +5 °C to +25 °C.

Note

The product information listed above has been compiled to the best of our knowledge and is based on current data. The properties mentioned are typical but therefore do not constitute a specification. The information provided does not relieve the customer of his obligation to test for suitability for the intended applications and processes. All specifications are subject to change without notice. Colour variations are possible.