

## WT-5415 Anti-slip tape, soft

Slip resistant surface and Slip class R10 according to DIN EN 16165

### PRODUCT AND APPLICATION DESCRIPTION

WT-5415 is a non-abrasive anti-slip tape suitable for wet areas. Due to the finely structured anti-slip coating without mineral grain, it is therefore particularly foot-friendly and ideal for barefoot areas and public facilities. WT-5415 is very robust, resilient and easy to clean. Furthermore, it is characterised by its high scratch resistance and durability.

- | For smooth surfaces indoors
- | For slip-resistant finishing of stairs, ladders, tiles, etc..
- | Can be used for sanitary areas and barefoot zones

### TECHNICAL DATA

Detail:				
Colour:		Transparent	Black/white	Other colours and individually printed
Carrier material:		PVC	PVC	PVC
Thickness: (without liner)		0.89 mm ± 0.5 mm	0.75 mm ± 0.5 mm	0.91 mm ± 0.5 mm
Liner:		Silicone paper	Silicone paper	Silicone paper
Adhesive:		Acrylat	Acrylat	Acrylat
Adhesive strength:		2.6 kg/inch	2.9 kg/inch	16 N / 24 mm
Slip resistance:		R10 according to DIN EN 16165	Slip resistant surface	R10 according to DIN EN 16165
Temperature resistance:		-5°C to +50°C	-5°C to +50°C	-5°C to +50°C
Application temperature:		≥ 12°C	≥ 12°C	≥ 12°C

### MORE INFORMATION

To achieve optimum adhesion, the substrate must be free from release agents such as greases, oils, surfactants, dirt and dust. The use of an adhesive primer is required on the following surfaces: concrete and asphalt, untreated, unpainted wood, and on all rough, grained surfaces. Store in a dry and UV-protected place at +5 °C to +25 °C.

#### Note

The product information listed above has been compiled to the best of our knowledge and is based on current data. The properties mentioned are typical but therefore do not constitute a specification. The information provided does not relieve the customer of his obligation to test for suitability for the intended applications and processes. All specifications are subject to change without notice. Colour variations are possible.