

WT-5543 High quality viscose fabric

PRODUCT AND APPLICATION DESCRIPTION

WT-5543 is a high-quality polymer-coated viscose fabric, combined with a strongly adhesive synthetic rubber-based pressure-sensitive adhesive. It is universally suitable for all standard requirements in repair and fastening work, as well as for labeling and bundling due to the variety of colors.

- ! High adhesion
- ! Pollutant-free, abrasion-resistant, aging-resistant
- ! Hand tearable and writeable



TECHNICAL DATA

Carrier material:	Polymer coated fabric cloth
Thickness: (without liner)	0.28 mm \pm 0.02 mm
Adhesive:	Synthetic rubber base
Adhesive strength to steel:	\geq 3,5 N/10 mm
Tensile strength:	\geq 80 N/10 mm
Temperature range:	-40°C to +105°C
Application temperature:	\geq 12 °C
Available colors:	Yellow, red, green, brown, grey, black, white, dark blue

FURTHER INFORMATION

To achieve the optimal adhesive strength, the substrate must be free from separating agents such as greases, oils, surfactants, dirt and dust. Immediately after unrolling, apply the tape to the surface and press it down firmly. The storage has to be dry and UV-protected between +5 °C and +25 °C.

Note

The product information listed above has been compiled to the best of our knowledge and is based on current data. The properties mentioned are typical but therefore do not constitute a specification. The information provided does not relieve the customer of his obligation to test for suitability for the intended applications and processes. All specifications are subject to change without notice. Colour variations are possible.