

## WT-5562 Fabric tape

### PRODUCT AND APPLICATION DESCRIPTION

WT-5562 is a PE-coated, dense, fine-threaded and waterproof synthetic silk fabric with a strong, shear-resistant, natural rubber adhesive with a very good aging resistance. It is ideal for splicing, fastening, bundling, repairing and sealing. Furthermore, it is available in many colors and perfect for marking in an industrial environment and as a quick, eye-catching marker for dangerous areas.

- ! Can be used for indoor and outdoor areas
- ! Matt, tear-resistant, abrasion-resistant, writable
- ! Also available in neon colors



### TECHNICAL DATA

Carrier material:	Rayon fabric, PE coated, matte
Thickness: (without liner)	0.3 mm
Adhesive:	Natural rubber
Tensile strength:	16 kg/25 mm
Temperature range:	up to +40 °C
Application temperature:	5°C to 35°C
Available colors:	Yellow, black, white, red, green, blue, brown, gray, neon yellow, neon orange, neon green, neon pink

### FURTHER INFORMATION

To achieve the optimal adhesive strength, the substrate must be free from separating agents such as greases, oils, surfactants, dirt and dust. Immediately after unrolling, apply the tape to the surface and press it down firmly. The storage has to be dry and UV-protected between +5 °C and +25 °C.

#### Note

The product information listed above has been compiled to the best of our knowledge and is based on current data. The properties mentioned are typical but therefore do not constitute a specification. The information provided does not relieve the customer of his obligation to test for suitability for the intended applications and processes. All specifications are subject to change without notice. Colour variations are possible.