

WT-5731 Glass fabric teflon slip tape

PRODUCT AND APPLICATION DESCRIPTION

WT-5731 is coated on one side with high temperature resistant silicone adhesive. A yellow, textured PVC release liner is applied to the adhesive surface to facilitate application. The tape is used as an easy release backing on heat sealing and packaging machines, ironing and pressing equipment, for covering drying cylinders, lining chutes and release surface on gluing tools.

- | Can be used for indoor and outdoor areas
- | Particularly low coefficient of friction
- | Extremely high resistance and mechanical strength



TECHNICAL DATA

Carrier material:	PTFE glass fabric
Thickness: (without liner)	0.125 mm
Adhesive:	Polysiloxane
Adhesive strength to steel:	27 N/50 mm
Temperature range:	-73°C to +260°C
Application temperature:	≥12 °C
Available colors:	Brown

FURTHER INFORMATION

To achieve the optimal adhesive strength, the substrate must be free from separating agents such as greases, oils, surfactants, dirt and dust. The storage has to be dry and UV-protected between +10 °C and +27 °C.

Note

The product information listed above has been compiled to the best of our knowledge and is based on current data. The properties mentioned are typical but therefore do not constitute a specification. The information provided does not relieve the customer of his obligation to test for suitability for the intended applications and processes. All specifications are subject to change without notice. Colour variations are possible.