

## WT-5810A space marking anti-slip

### PRODUCT AND APPLICATION DESCRIPTION

The polyurethane storage location markers are particularly robust and resistant. They are particularly suitable for applications where high adhesive strength is required. Characteristic is the anti-slip and retroreflective surface.

- | For smooth and textured floors indoors and outdoors
- | Suitable for pedestrians and lift trucks
- | Self-adhesive on a wide range of surfaces



### TECHNICAL DATA

Material:	Polyurethan
Thickness: (without liner)	1.6 mm ± 0.1 mm
Liner:	Silicone foil
Surface:	Retro-reflective
Slip class:	R11 according to DIN EN 16165
Adhesive:	Synthetic rubber
Adhesive property:	Permanent, extra strong
Temperature range:	-20 °C to +70 °C
Application temperature:	≥20 °C
Available colors:	Yellow, red, blue, green, black

### FURTHER INFORMATION

To achieve optimum adhesion, the substrate must be free from release agents such as grease, oil, surfactants, dirt and dust. The product should be stored dry and UV-protected at 20°C to 30°C.

#### Note

The product information listed above has been compiled to the best of our knowledge and is based on current data. The properties mentioned are typical but therefore do not constitute a specification. The information provided does not relieve the customer of his obligation to test for suitability for the intended applications and processes. All specifications are subject to change without notice. Colour variations are possible.