

## WT-5846 Durable floor marking tape

### PRODUCT AND APPLICATION DESCRIPTION

For marking roadways, work areas, safety areas and storage areas. Ideal for dry areas, quick to apply, extremely wear-resistant, can be driven over immediately, replaces marking with paint.

- | For smooth and textured floors indoor
- | Suitable for pedestrians and lift trucks
- | Suitable for concrete screed smooth, EP / PU / MMA coatings, tiles, concrete paving



### TECHNICAL DATA

Material:	Polyurethan (fabric reinforced)
Thickness: (without Liner)	1.1 mm
Liner:	Silicone foil
Surface:	Glossy
Adhesive:	Synthetic rubber
Adhesive property:	Permanent, extra strong
Temperature resistance:	-20°C to +70°C
Application temperature:	≥ 20°C
Available colours:	Yellow, red, blue, green, white

### MORE INFORMATION

It is possible to drive over the belt with floor conveyors. Turning and twisting on the tape with floor conveyors or similar heavy vehicles must be avoided and can lead to the destruction of the tape. To achieve optimum adhesion, the substrate must be free of release agents such as grease, oil, surfactants, dirt and dust. Store in a dry and UV-protected place at 20°C to 30°C.

#### Note

The product information listed above has been compiled to the best of our knowledge and is based on current data. The properties mentioned are typical but therefore do not constitute a specification. The information provided does not relieve the customer of his obligation to test for suitability for the intended applications and processes. All specifications are subject to change without notice. Colour variations are possible.