

WT-5848 Tactile floor marking tape - Guidance system for the blind

PRODUCT AND APPLICATION DESCRIPTION

The tactile floor marking tape enables blind and visually impaired people to find their way. The tape can be stuck to almost all solid surfaces. It is extremely wear-resistant, highly adhesive and has a non-slip surface with good grip even when wet.

- | For smooth and textured floors indoors and outdoors
- | Suitable for pedestrians and lift trucks
- | Suitable for concrete screed smooth, EP / PU / MMA coatings, tiles, concrete paving, asphalt



TECHNICAL DATA

Material:	Polyurethan
Thickness: (without Liner)	2,3 mm ± 0,5 mm
Liner:	Silicone paper
Surface:	Matte reflective
Adhesive:	Synthetic rubber
Adhesive property:	Permanent, extra strong
Temperature resistance:	-20 °C up to +70 °C
Application temperature:	≥12 °C
Available colours:	White

MORE INFORMATION

It is possible to drive over the belt with floor conveyors. Turning and twisting on the tape with floor conveyors or similar heavy vehicles must be avoided and can lead to the destruction of the tape. To achieve optimum adhesion, the substrate must be free of release agents such as grease, oil, surfactants, dirt and dust. Store in a dry and UV-protected place at 20°C to 30°C.

Note

The product information listed above has been compiled to the best of our knowledge and is based on current data. The properties mentioned are typical but therefore do not constitute a specification. The information provided does not relieve the customer of his obligation to test for suitability for the intended applications and processes. All specifications are subject to change without notice. Colour variations are possible.