

## WT-7110 Space marking

Version: CA01

### PRODUCT AND APPLICATION DESCRIPTION

Labels, stickers and signs made of polycarbonate are particularly robust and resistant. They are particularly suitable for applications where high adhesive strength is required. The nature and strength of the material allows the labels to be applied over recesses in the profile of trusses and storage racks.

- ! Suitable for labels, stickers and signs
- ! Extremely durable print
- ! Self-adhesive to a wide range of surfaces



### TECHNICAL DATA

Material:	Polycarbonate
Thickness: (without liner)	0.7 mm
Liner:	Silicone paper
Surface:	Silk matt
Adhesive:	Acrylic
Adhesive property:	Permanent
Mounting type:	self-adhesive
Temperature range:	-20 °C to +70 °C
Application temperature:	≥12 °C
Available colors:	Multicoloured, individually printed

### FURTHER INFORMATION

To achieve optimum adhesion, the substrate must be free from release agents such as grease, oil, surfactants, dirt and dust. The product should be stored dry and UV-protected at 10°C to 25°C.

#### Note

The product information listed above has been compiled to the best of our knowledge and is based on current data. The properties mentioned are typical but therefore do not constitute a specification. The information provided does not relieve the customer of his obligation to test for suitability for the intended applications and processes. All specifications are subject to change without notice. Colour variations are possible.