

Floor sign - foil, photoluminescent

Version: FN23

PRODUCT AND APPLICATION DESCRIPTION

Floor sign made of hard-wearing and durable foil with anti-slip surface. It is extra thin and easy to clean. The ideal marking in the dark or when there is a lot of smoke. The floor sign has an extra high luminance of 200/25 mcd/m² according to DIN 67510.

- | Suitable for pedestrian and pallet truck traffic
- | Quick attachment due to self-adhesive backside
- | Very good floor adhesion
- | Suitable for smooth indoor floors



TECHNICAL DATA

Material:	Plastic foil
Thickness: (without liner)	0.65 mm ± 0.1 mm
Liner:	Silicone foil
Surface:	Glossy
Adhesive:	Acrylic
Adhesive property:	Permanent
Slip resistance:	R10 according to DIN EN 16165
Luminance:	200/25 mcd/m ² (10 min/ 60 min) according to DIN 67510
Temperature range:	-20 °C up to +70 °C
Application temperature:	≥12 °C
Available colours:	Multicoloured, individually printed

FURTHER INFORMATION

To achieve optimum adhesion, the substrate must be free of release agents such as grease, oil, surfactants, dirt and dust. For exterior use, the substrate must be pre-treated with Primer No. 5 and follow the installation instructions. An additional edge sealant prevents the penetration of moisture. The product should be stored dry and UV-protected at 10°C to 25°C.



Note

The product information listed above has been compiled to the best of our knowledge and is based on current data. The properties mentioned are typical but therefore do not constitute a specification. The information provided does not relieve the customer of his obligation to test for suitability for the intended applications and processes. All specifications are subject to change without notice. Colour variations are possible.