

Floor sign - anti-slip, soft

Version: PA01

PRODUCT AND APPLICATION DESCRIPTION

Floor signs made of hard-wearing and durable PVC with a finely structured anti-slip surface. The anti-slip surface is very stable, resilient and easy to clean. The scratch-resistant print ensures long-lasting legibility of the motifs.

- | For smooth indoor floors
- | Suitable for pedestrian and pallet truck traffic
- | Quick application due to self-adhesive backing
- | Easy and quick to clean
- | Suitable for safety signs ASR A1.3

TECHNICAL DATA

Material:	PVC
Thickness: (without liner)	0.9 mm ± 0.5 mm
Liner:	Silicone paper
Surface:	Embossed, slightly shiny
Adhesive:	Acrylic
Adhesive property:	Permanent
Slip resistance:	R10 according to DIN EN 16165
Temperature range:	-5 °C to +50 °C
Application temperature:	≥12 °C
Available colours:	Multicoloured, individually printed

FURTHER INFORMATION

To achieve optimum adhesion, the substrate must be free from release agents such as greases, oils, surfactants, dirt and dust. The product should be stored dry and UV-protected at 10°C to 25°C.

Note

The product information listed above has been compiled to the best of our knowledge and is based on current data. The properties mentioned are typical but therefore do not constitute a specification. The information provided does not relieve the customer of his obligation to test for suitability for the intended applications and processes. All specifications are subject to change without notice. Colour variations are possible.