

Floor sign - anti-slip, outdoor

Version: PW08

PRODUCT AND APPLICATION DESCRIPTION

Floor signs made of hard-wearing and durable PVC with a finely structured anti-slip surface. The anti-slip surface is very stable, resilient and easy to clean. Permanent butyl adhesive for a strong bond to the floor.

- | Suitable for pedestrian and forklift traffic
- | Quick to attach due to self-adhesive backing
- | Very good floor bond
- | Suitable for indoor and outdoor use
- | Suitable for concrete paving and asphalt

TECHNICAL DATA

| | |
|----------------------------|-------------------------------------|
| Material: | PVC |
| Thickness: (without liner) | 1.3 mm ± 0.5 mm |
| Liner: | Silicone paper |
| Surface: | Embossed, matt |
| Adhesive: | Butyl rubber |
| Adhesive property: | Permanent |
| Slip resistance: | Slip resistance surface |
| Temperature range: | -5 °C to +50 °C |
| Application temperature: | ≥12 °C |
| Available colours: | Multicoloured, individually printed |

FURTHER INFORMATION

To achieve optimum adhesion, the substrate must be free of release agents such as grease, oil, surfactants, dirt and dust. For exterior use, the substrate must be pre-treated with Primer No. 5 and follow the installation instructions. An additional edge sealant prevents the penetration of moisture. The product should be stored dry and UV-protected at 10°C to 25°C.

Note

The product information listed above has been compiled to the best of our knowledge and is based on current data. The properties mentioned are typical but therefore do not constitute a specification. The information provided does not relieve the customer of his obligation to test for suitability for the intended applications and processes. All specifications are subject to change without notice. Colour variations are possible.