according to 1907/2006/EG, Article 31



Article no: 3051.25. **PRIMER No. 5**

 Print date:
 11.08.2025
 Processing date:
 11.08.2025

 Version:
 A082025
 Issue date:
 11.08.2025

10991 DE

SECTION 1: Identification of the substance/mixture and of the company

1.1 Product identifier

- Trade name: PRIMER No. 5
- UFI: 7WV0-20S1-A003-PYFA

1.2 Relevant identified uses of the substance or mixture and uses, which are advised against

- Use sector SU19 Construction
- Product category PC9a Coatings and paints, thinners, paint removers.

1.3 Details of the supplier providing the safety data sheet

- Manufacturer/Supplier:

1A Tapes GmbH Mittelstraße 9 07554 Korbußen

Informing department:

E-mail: info@1atapes.de

Tel: +49 36602 2891-00 (Mon - Thurs: 08:00 - 16:00, Fri: 08:00 - 14:30)

1.4 Emergency number:

Emergency number Tel: +49 36602 2891-00 This number is only manned during office hours.

SECTION 2: Potential hazards

2.1 Classification of the substance or mixture

- Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 2 H225 Highly flammable liquid and vapor.



Eye Irrit. 2 H319 Causes severe eye irritation. STOT SE 3 H336 May cause drowsiness and dizziness.

2.2 Label elements

- Labeling according to Regulation (EC) No. 1272/2008 The product is classified and labeled according to the CLP regulation.

- Hazard pictograms





GHS02

GHSO

- Signal word Danger
- Hazard-determining components of labeling: n-butyl acetate, butanone

Page 1/10 Continue on page 2

according to 1907/2006/EG, Article 31

A082025 ATAPES

Trade name: PRIMER No. 5

Hazard statements

H225 Highly flammable liquid and vapor.

H319 Causes severe eye irritation.

H336 May cause drowsiness and dizziness.

Safety advice

P210 Keep away from heat, hot surfaces, sparks, open flames

and other sources of ignition. Do not smoke.

P241 Use explosion-proof [electrical/ventilation/lighting] equipment. **P303+P361+P353** IF IN CONTACT WITH SKIN (or hair): Remove all contaminated

Remove all contaminated clothing immediately. Wash skin with water [or shower].

25-50%

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove any contact lenses if possible. Continue to rinse.

P405 Keep locked up.

P501 Dispose of contents/container in accordance

with local/regional/national/international regulations.

2.3 Other hazards

- Results of PBT and vPvB assessment

- PBT: Not applicable.- vPvB: Not applicable.

CAS: 78-93-3

SECTION 3: Composition/information on ingredients

butanone

3.2 Chemical characterization: Mixtures

- Description: Mixture of the following substances with non-hazardous admixtures.

Dangerous components	EINECS: 201-159-0 index number: 606-002-00-3	Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	
	CAS: 123-86-4 EINECS: 204-658-1 index number: 607-025-00-1	n-butyl acetate Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	25-50%
		•	
Most important components	CAS: 78-93-3 EINECS: 201-159-0	butanone	25-50%
	index number: 606-002-00-3	♠ Flam. Liq. 2, H225♠ Eye Irrit. 2, H319; STOT SE 3, H336	
	CAS: 123-86-4 EINECS: 204-658-1 index number: 607-025-00-1	n-butyl acetate	25-50%
		Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	
	CAS: 68131-99-7	PICCO A140/TER HCR P140 B	2,5-10%
	CAS: 25038-32-8	SIS polymer	2,5-10%
	CAS: 152698-66-3	C5 Hydrocarbon Polymer	2,5-10%

Additional information: Refer to Section 16 for the wording of the listed hazard statements.

SECTION 4: First aid measures

4.1 Description of first aid measures

After inhalation: fresh air supply, in case of complaints consult a doctor.
After skin contact: In general, the product is not irritating to the skin.

- After eye contact: Rinse opened eye for several minutes under running water.

Consult a doctor if symptoms persist.

- After ingestion: Consult a physician if symptoms persist.

4.2 Most important symptoms and effects, both acute and delayed

- No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed.

- No further relevant information available.

Page 2/10 Continue on page 3

according to 1907/2006/EG, Article 31

Trade name: PRIMER No. 5



SECTION 5: Fire fighting measures

5.1 Extinguishing media

- Suitable extinguishing media: CO2, sand, extinguishing powder. Do not use water.
- Unsuitable extinguishing media for safety reasons: Water in full jet.

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

5.3 Advice for fire-fighters

- Special protective equipment: No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions

Do not allow to enter drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomaceous earth, acid binders, universal binders, sawdust). Provide adequate ventilation.

Do not wash away with water or aqueous cleaning agents.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protective equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Protective measures for safe handling

Ensure good ventilation/exhaustion at the workplace.

Avoid formation of aerosols.

- Advice on protection against fire and explosion:

Keep ignition sources away - do not smoke.

Take measures against electrostatic charging.

7.2 Conditions for safe storage, taking into account incompatibilities.

- Storage: Requirements to be met by storerooms and receptacles: Store in a cool place.
- Information on storage in one common storage facility: Not required.
- Further information about storage conditions: Keep containers tightly closed.

Store in a cool, dry place in tightly closed containers.

- Storage class:
- -Classification according to the Ordinance on Industrial Safety and Health (BetrSichV): Flammable liquids

7.3 Specific end uses No further relevant information available.

SECTION 8: Exposure controls/personal protective equipment

8.1 Parameters to be monitored

Page 3/10 Continue on page 4

according to 1907/2006/EG, Article 31



Trade name: PRIMER No. 5

Ingredients with limit values that require monitoring at the workplace:		
CAS: 12	3-86-4 n-butyl acetate (25-50%)	
WEL	Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm	
CAS: 78-	-93-3 butanone (25-50%)	
WEL	Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm Sk, BMGV	

Ingredients with biological limit values:	
CAS: 78-9	3-3 butanone (25-50%)
BMGV	70 µmol/L Medium: urine Sampling time: post shift Parameter: butan-2-one

Additional notes: The lists valid at the time of preparation were used as a basis.

8.2 Exposure controls

- Personal protective equipment:

- General protective and hygienic measures:

Keep away from food, drink and animal feeding stuffs. Immediately remove contaminated, soaked clothing. Wash hands before breaks and at the end of work. Avoid contact with eyes.

Avoid contact with eyes and skin.

- Respiratory protection:

In case of short or low exposure, respiratory filter device; in case of intensive or prolonged exposure use self-contained breathing apparatus.

- Hand protection:

Use chemical resistant gloves based on butyl rubber with a minimum thickness of 0.7 mm and a permeability of at least 30 minutes according to EN 374. Check before use.

Take gloves neatly, without touching the outside with bare hands.

Dispose of used gloves immediately according to the rules.

Wash and dry hands.

- Eye protection:



Tight fitting safety glasses/goggles

Page 4/10 Continue on page 5



Trade name: PRIMER No. 5

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties **General information**

· Appearance:

Form:

Color: According to product name

· Odour:

· Odour threshold:

· Melting point/freezing point:

· Boiling point or initial boiling point and boiling

· Flammability

· Lower and upper explosion limit

· Lower: Upper: · Flash point:

· Auto-ignition temperature:

· Decomposition temperature:

Ha ·

· Viscosity:

· Kinematic viscosity · Dynamic at 20 °C:

· Solubility

· water

· Partition coefficient n-octanol/water (log value)

· Vapour pressure at 20 °C:

· Vapour pressure at 50 °C:

· Density and/or relative density

· Density at 20 °C: · Relative density · Vapour density

Fluid

Characteristic Not determined.

Undetermined.

79-80.5 °C (CAS: 78-93-3 butanone)

Highly flammable.

1.2 Vol % (CAS: 123-86-4 n-butyl acetate) 11.5 Vol % (CAS: 78-93-3 butanone) -4 °C (CAS: 78-93-3 butanone) 370 °C (CAS: 123-86-4 n-butyl acetate)

Not determined.

Mixture is non-polar/aprotic.

Not determined. 100 mPas

Not miscible or difficult to mix.

Not determined.

105 hPa (CAS: 78-93-3 butanone)

55 hPa

0.869 g/cm³ Not determined. Not determined.

9.2 Other information No further relevant information available.

Appearance:

· Form: Fluid

Important information on protection of health and environment, and on safety.

· Ignition temperature: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures

are possible.

· Solvent content:

· Organic solvents: 76.0 % · VOC (EC) 76.00 % · Solids content: 23.3 %

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard classes

· Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void

Highly flammable liquid and vapour. · Flammable liquids

· Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable

Void gases in contact with water · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void · Desensitised explosives Void

Page 5/10 Continue on page 6 according to 1907/2006/EG, Article 31

Trade name: PRIMER No. 5



SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

- Thermal decomposition / conditions to be avoided:

No decomposition if used as directed.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

- Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:		
ATE (Acute Toxicity Estimate)		
Inhalation	LC50/4 h	114 mg/l

Primary irritant effect:

- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation

Causes severe eye irritation.

- Respiratory/skin sensitization

Based on available data, the classification criteria are not met.

- Additional toxicological information:
- CMR effects (carcinogenic, mutagenic and toxic for reproduction).
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- Specific target organ toxicity (single exposure)

May cause drowsiness and dizziness.

- Specific target organ toxicity in case of repeated exposure

Based on available data, the classification criteria are not met.

- Aspiration hazard Based on available data, the classification criteria are not met.
- 11.2 Information on other hazards*

Endocrine disrupting properties		
CAS: 78-93-3	butanone	List II

Page 6/10 Continue on page 7

Trade name: PRIMER No. 5

according to 1907/2006/EG, Article 31



SECTION 12: Environmental information

12.1 Toxicity

- Aquatic toxicity: No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11
- 12.7 Other adverse effects
- Further ecological information:
- General information:

Water hazard class 2 (Self-assessment): clearly hazardous for water.

Do not allow to enter ground water, water courses or sewage system.

Hazardous to drinking water even if small quantities leak into the ground.

SECTION 13: Notes on disposal

- 13.1 Waste treatment method
- **Recommendation:** Must not be disposed of together with household waste. Do not allow to enter drains.
- Uncleaned packaging:
- **Recommendation:** Dispose of in accordance with official regulations.

Page 7/10 Continue on page 8

Trade name: PRIMER No. 5

according to 1907/2006/EG, Article 31

according to 1907/2000/EG, Article 3



SECTION 14: Transport information

14.1 UN number

- ADR, IMDG, IATA UN1263

14.2 UN proper shipping name

- ADR PAINT
- IMDG, IATA PAINT

14.3 Transport hazard classes

- ADR, IMDG, IATA



- Class 3 Flammable liquids

- Hazard label 3

14.4 Packing group

- ADR, IMDG, IATA

14.5 Environmental hazards: Not applicable.

14.6 Special precautions for the user

Caution: Flammable liquid.

- Hazard identification number (Kemler-

number):33- EMS number:F-E,S-E- Stowage CategoryB

14.7 Transport in bulk according to Annex II of the MARPOL Convention and according to the IBC Code

MARPOL Convention and according to the IBC Code Not applicable.

- Transport/further information:

- ADR

- Limited Quantity (LQ)- Excepted Quantities (EQ)5LCode: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

- Transport category 2
- Tunnel restriction code D/E

- IMDG

- Limited quantities (LQ)- Excepted quantities (EQ)5LCode: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

55.0

- UN Model Regulation: UN 1263 COLOR, 3, II

Page 8/10 Continue on page 9

according to 1907/2006/EG, Article 31



SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific to the substance or mixture. substance or mixture

- Directive 2012/18/EU

Trade name: PRIMER No. 5

- Named dangerous substances ANNEX I None of the ingredients are included.
- Seveso category P5c FLAMMABLE LIQUIDS
- Quantity threshold (in tonnes) for use in lower tier establishments 5,000 t
- Quantity threshold (in tons) for use in upper-tier establishments 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Restriction conditions: 3

Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and **Electronic equipment - Annex II**

None of the ingredients are included.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPORT SUBSTANCES FOR EXPLOSIVE SUBSTANCES (Upper concentration limit for a permit under Article 5(3))

None of the ingredients are included.

Annex II - REPORTABLE EXPORT SUBSTANCES FOR EXPLOSIVES

None of the ingredients are included.

Regulation (EC) No. 273/2004 on drug precursors		
CAS: 78-93-3	Butanon	3

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade in drug precursors between the Community and third countries		
CAS: 78-93-3	Butanon	3

- National (germany) regulations:
- Technical Instructions on Air:

Class	Share in %	
NK	50-100	

- Water hazard class: WGK 2 (Self-assessment): clearly hazardous for water.
- 15.2 Chemical safety assessment: A chemical safety assessment has not been carried out.

SECTION 16: Other information

The information provided is based on our present knowledge, but does not constitute a guarantee of product properties and of product characteristics and do not establish a contractual legal relationship.

- Relevant sentences

H225 Highly flammable liquid and vapor.

H319 Causes severe eye irritation.

H332 Harmful by inhalation.

H336 May cause drowsiness and dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

- Department issuing data sheet: Product safety department.
- Contact person: T. Degenhardt

Page 9/10 Continue on page 10

according to 1907/2006/EG, Article 31

A082025 ATAPES

Trade name: PRIMER No. 5

- Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route. (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Dangerous Goods Code

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

GefStoffV: Ordinance on Hazardous Substances (Germany)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very persistent and very bioaccumulative

Flam. Lig. 2: Flammable liquids - Category 2

Acute Tox. 4: Acute toxicity - Category 4

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

- * Data changed from previous versionw