

WT-5234 PET high temperature tape

The WT-5234 is a one-sided adhesive polyester tape with a high-performance silicone adhesive. It can be removed without leaving any residue.

Applications: Indoor

Technical specifications

Material: Polyester

Thickness: 0,06 mm

Glue: Silicone glue

Adhesive power: 7,5 N / 25 mm

Tensile force:

Dynamic shear:

Temperature resistance: -73 °C to 200 °C

Processing temperature:

Storage:



Available colours

- Transparent
- Yellow
- Red
- Light blue
- Blue
- Light green
- Green
- Purple
- Orange
- Brown
- Pink
- White
- Light grey
- grey
- Dark grey
- Black
- Black/White
- Yellow/Black
- Red/White
- Blue/White
- Green/White
- Photoluminescence
- Photoluminescence/Black

Applications

- Concrete / smooth
- EP-/ Pu / MMA coating
- EP-/ Pu / MMA coating antislip
- Tiles
- Concrete paving
- Asphalt

Application information

The WT-5234 is suitable for a variety of industrial and electrical industry applications, e.g.

For covering and fixing at high temperatures, such as circuit boards, in powder coating or for the production of stamped parts.

Note / Information

The product information listed above is compiled to the best of our knowledge and based on current data. These characteristics are typical, but they do not constitute a specification. The information provided to the customer does not relieve the customer of his obligation to test for suitability for the intended applications and procedures.

Date:
21.09.2020

Certified
DIN ISO 9001: 2015
Reg.-Nr. 310651 QM15



Tel.: +49 36602 2891-00
Fax: +49 36602 2891-99
eMail: info@1tapes.de

1A Tapes GmbH
Mittelstraße 9
07554 Korbußen