

## WT-4210 - Double-sided adhesive tape

Double-sided adhesive tape with very high adhesive force.

Applications: Indoor & Outdoor

### Technical Specification

Material:	PET film
Substrate thickness:	
Thickness:	0,2 mm
Liner type:	
Glue:	Acrylic
Adhesive power:	≥ 17 N / 24 mm
Dynamic shear:	
Tensile force:	49N / 25 mm
Dynamic shear:	50%
Temperature resistance:	-30°C to +120°C
Processing temperature:	+18°C to +25°C
Storage:	



#### Available colours

- Transparent
- White
- Gray
- Black
- Amber

#### Technical information

Suitable for use on many plastics such as ABS, PP etc., for all smooth and rough plastics and metals. Translucent for visible bonds. Very good shear strength.

#### Note / Information

In the industry for bonding ABS, various films, plastic parts and heatable mirrors, metals and other materials. Suitable for outdoor use.

The product information listed above is compiled to the best of our knowledge and based on current data. These characteristics are typical, but they do not constitute a specification. The information provided to the customer does not relieve the customer of his obligation to test for suitability for the intended applications and procedures.

Date:  
14.10.2020

Certified  
DIN ISO 9001: 2015  
Reg.-Nr. 310651 QM15



Tel.: +49 36602 2891-00  
Fax: +49 36602 2891-99  
eMail: info@1atapes.de

1A Tapes GmbH  
Mittelstraße 9  
07554 Korbußen