

## WT-5231 One-sided adhesive polyimid tape

The WT-5231 is ideal for use in high temperature areas. It is characterized by high heat resistance and can be removed again without leaving any adhesive residue.

Applications: Indoor

### Technical Specification

Material: Polyimide-Film

Substrate thickness: 25 µm

Thickness: 70 µm

Liner type:

Glue: Silicone

Adhesive power: 6 N / 25 mm

Dynamic shear:

Tensile force: 15 - 17 kg / 25 mm

Dynamic shear:

Temperature resistance: -50 °C to +180 °C, short terms to +250 °C

Processing temperature:

Storage:



Derzeit leider kein Foto vorhanden.

### Available colours

- Transparent
- White
- Gray
- Black
- Amber

### Technical information

The WT-5231 has a high UV resistance. It is suitable for covering and fixing at high temperatures and for electrical insulation.

### Note / Information

The product information listed above is compiled to the best of our knowledge and based on current data. These characteristics are typical, but they do not constitute a specification. The information provided to the customer does not relieve the customer of his obligation to test for suitability for the intended applications and procedures.

Date:  
21.09.2020

Certified  
DIN ISO 9001: 2015  
Reg.-Nr. 310651 QM15



Tel.: +49 36602 2891-00  
Fax: +49 36602 2891-99  
eMail: info@1tapes.de

1A Tapes GmbH  
Mittelstraße 9  
07554 Korbußen