

## WT-7110 - space marker

Durable, durable, self-adhesive floor marking. Ideal for dry areas, quick to stick on, wear-resistant, easy to clean, immediately passable, replaces the marking with paint.

Applications: Indoor

## Technical specifications

Material: Polycarbonate

Thickness: 0,7 mm

Glue: Acrylic

Adhesive power:  $\geq 16$  N / 2,5 cm


Tensile force: 180 N / 25 mm

Dynamic shear: 5 bis 10%

Temperature resistance: -20°C to +55°C

Processing temperature: +15°C to +25°C

Storage: trocken bei +5°C bis 25°C, UV-geschützt



## Available colours

- Transparent
- Yellow
- Red
- Light blue
- Blue
- Light green
- Green
- Purple
- Orange
- Brown
- Pink
- White
- Light grey
- grey
- Dark grey
- Black
- Black/White
- Yellow/Black
- Red/White
- Blue/White
- Green/White
- Photoluminescence
- Photoluminescence/Black

## Applications

- Concrete / smooth
- EP-/ Pu / MMA coating
- EP-/ Pu / MMA coating antislip
- Tiles
- Concrete paving
- Asphalt

## Application information

When laying the tape, the surface must be clean, free from grease, dust and dry. We recommend that you label the laying line with chalk first.

## Note / Information

It is possible to drive over the belt with floor conveyors. Turning and turning on the conveyor with floor conveyors or similar heavy vehicles should be avoided.

The product information listed above is compiled to the best of our knowledge and based on current data. These characteristics are typical, but they do not constitute a specification. The information provided to the customer does not relieve the customer of his obligation to test for suitability for the intended applications and procedures.

Date:  
21.09.2020

Certified  
DIN ISO 9001: 2015  
Reg.-Nr. 310651 QM15



Tel.: +49 36602 2891-00  
Fax: +49 36602 2891-99  
eMail: info@1tapes.de

1A Tapes GmbH  
Mittelstraße 9  
07554 Korbußen